instead of the radio. Hand signals, placards, high frequency radiotelephone, voice, flags, whistle or horn may be employed by an authorized officer or CCAMLR inspector, and message blocks may be dropped from an aircraft.

- (3) If other communications are not practicable, visual signals may be transmitted by flashing light directed at the vessel signaled. USCG units will normally use the flashing light signal "L" which, in the International Code of Signals, means "you should stop your vessel instantly."
- (4) Failure of a vessel's operator promptly to stop the vessel when directed to do so by an authorized officer or CCAMLR inspector, or by an enforcement vessel or aircraft, using loudhailer, radiotelephone, flashing light, flags, whistle, horn or other means constitutes prima facie evidence of the offense of refusal to allow an authorized officer or CCAMLR inspector to board.
- (5) A person aboard a vessel who does not understand a signal from an enforcement unit and who is unable to obtain clarification by loudhailer or radiotelephone must consider the signal to be a command to stop the vessel immediately.
- (c) Boarding. The operator of a vessel directed to stop must:
- (1) Monitor Channel 16, VHF-FM, if so equipped.
- (2) Stop immediately and lay to or, if appropriate and/or directed to do so by the authorized officer or CCAMLR inspector, maneuver in such a way as to allow the safe boarding of the vessel by the authorized officer or CCAMLR inspector and the boarding party.
- (3) Except for those vessels with a freeboard of 4 ft (1.25 m) or less, provide a safe ladder, if needed, for the authorized officer or CCAMLR inspector and boarding party to come aboard.
- (4) When necessary to facilitate the boarding or when requested by an authorized officer or CCAMLR inspector, provide a manrope or safety line, and illumination for the ladder.
- (5) Take such other actions as necessary to facilitate boarding and to ensure the safety of the authorized officer or CCAMLR inspector and the boarding party.

- (d) Signals. The following signals, extracted from the International Code of Signals, may be sent by flashing light by an enforcement unit when conditions do not allow communications by loudhailer or radiotelephone. Knowledge of these signals by vessel operators is not required. However, knowledge of these signals and appropriate action by a vessel operator may preclude the necessity of sending the signal "L" and the necessity for the vessel to stop instantly.
- (1) "AA" repeated (.- .-) is the call to an unknown station. The operator of the signaled vessel should respond by identifying the vessel by radiotelephone or by illuminating the vessel's identification.
- (2) "RY-CY" (.-. -.-- -.-. -.-) means "you should proceed at slow speed, a boat is coming to you." This signal is normally employed when conditions allow an enforcement boarding without the necessity of the vessel being boarded coming to a complete stop, or, in some cases, without retrieval of fishing gear that may be in the water.
- (3) "SQ3" (... --.- ...-) means "you should stop or heave to; I am going to board you."

Subpart B—High Seas Fisheries

AUTHORITY: 16 U.S.C. 5501 et seq.

§ 300.10 Purpose.

This subpart implements the High Seas Fishing Compliance Act of 1995 (Act), which requires the Secretary to license U.S. vessels fishing on the high seas.

§ 300.11 Definitions.

In addition to the terms defined in section 300.2 and those in the Act and the Agreement to Promote Compliance with International Conservation and Management Measures by Fishing Vessels on the High Seas, adopted by the Conference of the Food and Agriculture Organization of the United Nations on November 24, 1993 (Agreement), the terms used in this subpart have the following meanings. If a term is defined differently in §300.2, the Act, or the Agreement, the definition in this section shall apply.